JACK STANDS

wurtec
wurtec.com



Part Number: 11-535
Jack Stand

PRODUCT DESCRIPTION

Wurtec Jack Stands provide stable, adjustable support for elevator cars and counterweights during maintenance and service operations.

Designed for use in pairs, the stands secure to elevator guide rails and support loads up to 10,000 lb (4,536 kg) when equally loaded.

Featuring an adjustable height range of 4.5–7 ft (1.37–2.13 m), Wurtec Jack Stands accommodate various hoistway configurations and guide rail sizes. Their rail-mounted design allows elevator cars or counterweights to be lowered onto the stands while personnel remain outside the pit.

KEY FEATURES

- Supports up to 10,000 lb (4,536 kg) per equally loaded pair.
- Adjustable height range of 4.5–7 ft (1.37–2.13 m).
- Compatible with T89, T127-1, T127-2, and T140-1 guide rails.
- Rail-mounted design provides secure vertical positioning.
- Threaded jack bolts allow fine height adjustments for balanced load distribution.
- Designed to support elevator cars and counterweights during maintenance and service.

1.800.837.1066 | wurtecsales@wurtec.com

Revision 02 | 10/2026

JACK STANDS

wurtec
wurtec.com

PRODUCT SPECIFICATIONS

Product	Jack Stands
Rated Capacity	10,000 lbs (4,536 kg) per pair*
Minimum Height	4.5 ft (1.37 m)
Maximum Height	7 ft (2.13 m)
Weight	63 lb (28.6 kg)
Compatible Rail Sizes	T89 (8 lb), T127-1 (12 lb), T127-2 (15 lb), T140-1 (18.5 lb)

**Rated capacity applies when the load is equally distributed between both stands.*

1.800.837.1066 | wurtecsales@wurtec.com
Revision 02 | 10/2026